

CM-801F

Order No. 0235900

Electret earband microphone

- Ultra-light earband microphone for stage and podium
- Optimum speech intelligibility
- Movable drip ring
- Screwed-on cable, easy to replace
- Clip for strain relief; makes microphone more comfortable to wear and enhances stable positioning
- Other connection cables are available at option
- Supplied with bag and windshield

Model	CM-801F
Polar pattern	omnidir.
System	electret
Audio frequency range	60-15,000 Hz
Nominal impedance	1.8 kΩ
Sensitivity	6.3 mV/Pa
Max. sound pressure	130 dB
Power supply	pocket transmitters of the IN/PT/UF series or PS-500
Weight	16 g
Connection	4-pole mini XLR (optional: 3.5 mm stereo plug, 3-pole mini XLR or 4-pole Hirose connector)



CM-214U

Order No. 0236440

Electret headband microphone

- For stage, presentations and general speech applications
- Cardioid polar pattern and a vibration-reducing cartridge support allow for maximum protection against acoustic feedback and ensure minimum structure-borne noise
- Adjustable headband
- Secure fit, very comfortable to wear
- Supplied with a 4-pole mini XLR connection cable for connection to pocket transmitters of the IN/PT/UF series
- Supplied with bag and windshield

Model	CM-214U
Polar pattern	cardioid
System	electret
Audio frequency range	30-18,000 Hz
Nominal impedance	680 Ω
Sensitivity	4 mV/Pa
Max. sound pressure	130 dB
Power supply	pocket transmitter of the IN/PT/UF series or PS-500
Weight	40 g
Connection	4-pole mini XLR



HSE-340/SK

Order No. 1000026



Professional headband microphone, with cardioid polar pattern and a high-quality sound which is suitable for any vocal or speech application. Innovative design features ensure a maximum suppression of both the impact sound and structure-borne noise as well as an extra low acoustic feedback, very comfortable to wear. Beige version.

- Corrosion-resistant neckband, easy to clean
- Drip ring (protects cartridge from moisture)
- Unobtrusive and secure fit due to cable routing in neck area incl. strain relief and cable bending protection
- Stable positioning

Model	HSE-340/SK
Polar pattern	cardioid
System	electret
Audio frequency range	50-18,000 Hz
Nominal impedance	2 kΩ
Sensitivity	2.3 mV/Pa
Max. sound pressure	120 dB
Power supply	1.5-9 V
Weight	18 g (w/o cable and plug)
Connection	4-pole mini XLR

- Microphone windshield
- 4-pole mini XLR inline jack for connection to pocket transmitters from JTS or a pocket transmitters of the same design from other brand manufacturers



NM-43

Order No. 0235070

Neckband

- Matching the lavalier microphone CM-501
- Adjustable
- Lightweight plastic version

Supplied w/o microphone.



PT-RMS

Order No. 0236870

External mute button (cough button)

- For tie clip microphones and headband microphones from JTS
- Selectable switching mode (ON/OFF, momentary ON, momentary OFF)
- 4-pole mini XLR connection
- Compatible with any pocket transmitter from JTS

